

ProCon

TILE ADHESIVES

HIGH PERFORMANCE BONDING FOR STRONG & DURABLE FIXING



T1 — Standard Tile Adhesive

CEMENT BASED • ECONOMICAL SOLUTION

A reliable cement-based adhesive for fixing ceramic and porous tiles in interior areas — strong bonding with easy application, ideal for everyday residential tiling.

APPLICATIONS

- Ceramic tiles, floors & walls
- Small format tiles (up to 300x300mm)
- Residential rooms, kitchens

KEY SPECS

- Coverage: 55–60 sq.ft / 20kg
- Open Time: ~20 minutes
- Tensile Adhesion: ≥ 0.5 N/mm²

INTERIOR USE



T2 — Premium Tile Adhesive

POLYMER MODIFIED • WATER RESISTANT

A polymer-modified premium adhesive for fixing vitrified and low-porosity tiles, with enhanced bonding strength, water resistance & durability for internal & external use.

APPLICATIONS

- Vitrified & porcelain tiles
- Bathrooms, kitchens & balconies
- Medium tiles (600x600mm)

KEY SPECS

- Coverage: 50–55 sq.ft / 20kg
- Open Time: ~20 minutes
- Tensile Adhesion: ≥ 1.0 N/mm²

INTERNAL & EXTERNAL



T3 — High Performance Tile Adhesive

HIGHLY POLYMER MODIFIED • ANTI-SLIP

A high-performance adhesive built for demanding applications — large format tiles, tile-on-tile fixing & vertical installations — with excellent flexibility & anti-slip properties.

APPLICATIONS

- Tile-on-tile renovation work
- Large format tiles (>600x600mm)
- Exterior walls & cladding

KEY SPECS

- Coverage: 45–50 sq.ft / 20kg
- Slip Resistance: <0.5mm
- Tensile Adhesion: ≥ 1.25 –1.5 N/mm²

EXTERIOR & HIGH-RISE

ProCon by PROFITS CONNECTION



PREMIUM QUALITY POLYMER MODIFIED CEMENT PLASTER

READY MIX PLASTER

ProCon Ready Mix Plaster is manufactured using high-quality cement, graded sand and special additives to deliver smooth finishes, superior bonding and long-lasting durability. It ensures consistent quality, faster application and reduced material wastage compared to conventional site-mixed plaster — making it ideal for **residential, commercial and industrial projects**.

KEY FEATURES

- ✓ **High Strength**
- ✓ **Smooth Surface Finish**
- ✓ **High Coverage**
- ✓ **Economical Solution**
- ✓ **Crack Resistant**
- ✓ **Excellent Water Retention**
- ✓ **Faster Application**
- ✓ **Long Lasting Durability**



TECHNICAL SPECIFICATIONS

Appearance	Greyish Granular Powder
Max Aggregate Size	< 3 mm
Bulk Density	1.5 – 1.6 Kg/L
Compressive Strength	> 9 N/mm ² (28 days)
Water Retentivity	≥ 95%
Coverage	18–20 Sq.ft / 40 Kg Bag
Water Requirement	Approx. 6.5–7.0 L / 40 Kg Bag
Pot Life	1.5 – 2 Hours
Application Thickness	Up to 12 mm per Coat

APPLICATIONS

Internal & External Wall Plastering • Brick Masonry • AAC Block Masonry • Residential & Commercial Projects

PACKAGING: 40 KG BAG

ProCon by PROFITS CONNECTION

+91 70165 02523

business@profitsconnection.com

www.profitsconnection.com

T-12, 3rd Floor, Golden Square, Bholav, Bharuch-392001, Gujarat, India